

Boonton Power Analyzer Release Notes

Version 4.0	Incorporates new high-performance API. Enables single or multi-channel measurements of simulated pulsed or bursted signals with no, light, moderate, or heavy modulation and/or compression and various power levels. Utilizes a more user-friendly, streamlined installer. Transitions versioning from date code to sequence-based versioning.
20180817 Ver 3.2.6	Made the firmware installation feature more robust.
20180212 Ver 3.2.4.0	Added support for RTP4106.
20170206 Ver 3.0.12.0	Added Continuous capture mode for Measbuff feature. Added support for saving default virtual power analyzer configuration. Added Multi-Pulse analysis. The installer now has the ability to detect if IVI Shared components is already installed and skip installing this prerequisite if not needed. Added support for RTP Series model numbers. Added support for SaveUserCal method. Added SCPI commands for clearing and saving user cal. Various bug fixes and enhancements.
20160314 Ver 2.3.6.0	Added measurement buffer capability. Added internal modulation mode. *Requires firmware version 20160314 or greater. Added memory channels. Added trigger out mode command. Added code to update trigger delay when trigger position was changed. Added firmware Update capability (including a web check for new versions). Added the ability to select time base reference output for testing in the GUI. Added the ability to check for new versions of the PPAS and the ability to download and update to the new version.
	The following are GUI-only features: Added Autoset feature. Added Cal factor display. Added channel swapping capability. Trig out mode and memory channels added. Added logging capability. Added modulated mode. Added the ability to save trace graph as CSV. Various bug fixes and enhancements.
20150329 Ver 2.2.0.0	Added persistence displays. Added SCPI console window. Enabled separate windows for CCDF graphing and control. Various bug fixes and enhancements.



Boonton CommAgility Microlab Noisecom

20141114 Added a sensor information window to view sensor information, calibration factors, and hardware statistics (temps and voltages).

Added collapsible regions to the channel control and timebase windows. Added peak hold functionality.

Changed zoom function to use trigger delay instead of trigger position. Added printing and PDF support to multiple windows.

Optimized view area for CCDF graph. Various bug fixes and enhancements.



25 Eastmans Road Parsippany, New Jersey 07054

20140918 Initial Release Ver 2.1.3.0